

# SPECIFICATION SHEET



## 6 LITRE UN POLYCOMPOSITE DRUM (Reduced top for stacking)

A stackable UN Steel drum with a HDPE liner suitable for chemical products and food contact.

### Specification

#### Outer Steel

- Closure Security closure V1G2 made from PP in the top
- Gasket PE synthetic rubber 5mm between inner liner wall
- Handle 5mm Galvanised Wire Handle
- Body Straight Sided
- Top / Bottom Double seamed to body.
- External Coating RAL 5010
- Embossed Base UN6HA1/X/300/year
- Reduced Top 222mm Outside Diameter



200 mm

← 235 mm →

#### Internal Plastic Liner

- Inner Liner Tighthead inner liner made from HDPE Lupolen 4261A
- Liner Weight 250g
- Closure 2" Threaded Plug
- Closure Torque Min 12 Nm

Volume	Steel Plate Thickness (mm)			Weight	UN Approval
	Top End	Body	Bottom		
6 Litre Nominal	0.5mm	0.5mm	0.5mm	1.3 kg +/- 5%	UN6HAA1/X/300/**/ D/BAM3039-GDH

Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
100	CP1	Yes	NO	NO	NO	NO

*N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained.*

*Information on terms & conditions can be found on [www.jamesgcarrick.com](http://www.jamesgcarrick.com)*

This document is uncontrolled when printed.

James G Carrick & Co Ltd  
450 Petershill Road  
Springburn  
Glasgow  
G21 4PB

Tel +44 141 558 6008  
Fax +44 141 557 0318  
e mail [sales@jamesgcarrick.com](mailto:sales@jamesgcarrick.com)